NEW TECHNOLOGIES.
NEW SOLUTIONS.



FROM NAPCO









GEMINI"











Napco Commercial™ Gemini Combo. 24V Analog, Addressable Fire/Burglary Panel	
Napco Commercial™ GEMC Combo. Fire/Burglary and Burglary Configurations and Components	
Configurations Diagram: Napco Commercial™ GEMC Combo. Fire/Burglary and Burglary	4, 5
Napco Commercial™ Firewolf™ Analog Addressable 24V Fire Systems Configurations and Components	6, 7
Configurations Diagram: Firewolf™ Analog Addressable 24V Fire Systems	
Firewolf Conventional Fire/Life Safety Devices	8
Bridge® Remote Services Introduction, Touchscreen Tablet, Virtual Keypad, Z-Wave Home Controls & Integrated iSee Video™	9, 10, 11
Gemini™ iRemote™ Virtual Keypad	12
See Video Introduction, Cameras, Internet Video Recorder, Gateway	13, 14, 15
Configurations Diagram: iSee Video	16, 17
Gemini™ Keypads	18, 19
Gemini™ Panels	20, 21
Comparison & Configurations Chart: Gemini Panel Features by Model	22, 23
Napco Alternative Alarm Reporting Solutions: Up/Downloadable StarLink™ GSM Alarm Internet Communicator;	
NetLink™ Internet Alarm Communications	•
GeminiAccess™ Add-on Access Control and PCD-Manager	
Gemini Crystal-Control Wireless Transmitters & Receivers	28, 29
Configurations Diagram: Gemini System Builder	30, 31
Napco Wired Motion Sensors	
Napco Access Control Systems for 2 to 128 Doors	
Napco Commercial & Government Solutions Group	
Napco Fusion™ - Unique Total Integrated Security Solution for Intrusion, Fire, Video, Access & Locking	36
Napco Security Technologies. Four Divisions	(inside back cover)

About Napco:



Napco has a long heritage in the professional security community, dedicated to developing innovative technology and reliable security solutions and, including some of the industry's best-known

brands, such as Napco Security, Continental Access, Alarm Lock and Marks USA, and their most popular lines, Gemini intrusion and fire systems, iSee Video™ remote services, CardAccess enterprise-class access systems; Trilogy standalone & networked Networx code- and Prox-ID access locks; plus, Marks USA's architectural, commercial & institutional locksets.



Napco Security Technologies, Inc. (NASDAQ: NSSC) is ISO9001:2000 Certified and subscribes to a rigorous quality management system. Its products are precision-manufactured to exceed industry specs. and to last. Today, they protect millions of people, businesses, institutions & residences around the world.

NAPCO I COMMERCIAL

Gemini 24V Fire/Burg "Combo." Panel



More analog, commercial wireless and conventional input and output device types than any brand (just a few shown).

The 1st AHJ-Friendly, Analog Addressable in its Class.

GEMC Combination Fire & Burglary - 2 Systems in 1: More cost-effective, for more competitive bids, armed with a single all-in-one fire/burg combo. system, engineered to provide the same NFPA 72 & UL 9th ed. code-compliance & circuitisolation that was formerly only possible installing 2 separate burg and fire panels.

Features:

- ✓ The only integrated 24 Volt combo. system that works like two separate burg and fire panel installations in one, with independent pre-isolated circuits and power reserves
- ✓ 32 to 255 points of analog, addressable, commercial wireless and/or conventional 12V devices

- ✓ Award-Winning: Judged "Best in Fire/Life Safety", Security Industry Association, New Product Showcase (NPS), 2011
- ✓ More value, out-of-the-box-ready for lower equipment and labor costs
- ✓ More on-board power, 7A



- ✓ 4 NAC circuits onboard, expandable to 24
- ✔ Built-in Horn Strobe Synchronization (Wheelock & System Sensor protocol)
- ✔ Built in Dual line Phone Module and TCP/IP option
- ✓ More standby power in the can (32AH@24V)
- Printable AHJ reports of analog device sensitivity settings with current readings (uploadable)
- More analog, commercial wireless and conventional input and output device types than any other brand
- ✓ Compliances NFPA 72, UL Commercial Fire, UL864 9th Ed., SIA CP01, UL985. UL household & commercial burg.: UL1610, UL609, UL365, UL1023. NYC FD, CSFM (fire).

Napco Commercial™ GEMC Combo. Fire/Burglary and Burglary Configurations and Components:



GEMC-COMBO255KT 255 Point GEM-C Commercial Combo. Fire/Burg System Kit

- 24V Panel, 255 Points via commercial addressable, wireless or conventional fire or burg. devices, 4 on board NACs, 8 partitions (No Loop Isolator/Extender required)
- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.) Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Keypad (GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)



GEMC-COMBO128KT 128 Point GEM-C Commercial Combo. Fire/Burg System Kit

- 24V Panel, 128 Points via commercial addressable, wireless or conventional fire or burg. devices, 4 on board NACs, 8 partitions (No Loop Isolator/Extender required)
- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.). Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Keypad(GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)



GEMC-COMBO32KT 32 Point GEM-C Commercial Combo. Fire/Burg System Kit

- 24V Panel, 32 Points via commercial addressable, wireless or conventional fire or burg. devices, 2 on board NACs, 8 partitions (No Loop Isolator/Extender required)
- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.). Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Keypad (GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)



Napco Commercial GEMC Burglary (Only) GEMC-BURG96KT 96pt GEMC Addressable Commercial Burglary System Kit

- 24V Panel, 96 Points via commercial addressable, wireless or conventional burg. devices, 7 partitions
- Locking, Medium White Enclosure, 16 x 17" door, with 14.25" x 16" base (flush or surface mount.). Houses up to 16Ah battery backup.
- 4 Amp, 24V Power Supply
- Addressable SLC Burg Module, supports up to 96 addressable SLC burg devices (GEMC-BSLC)

- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading
- Menu-driven LCD Burglary Keypad with built-in 4 zone EZM, mounts anywhere on bus (GEMC-BK1)

7Amp NAC Extender for Universal FACP use or with GEMC Systems

GEMC-NAC7S

- 7 Amps of Power for use with NAPCO or other FACP panel brands
- 4 onboard NACs with up to 2A ea. expandable for up to 24 per system
- Regulates 24V auxiliary power
- Distributes synched bell and strobe outputs with built-in module
- Monitors AC, battery trouble, tamper and ground fault on Napco bus or provides universal FACP support
- Red locking enclosure, accommodates up to 16Ah total battery capacity



12VDC Burglary Power Supply for GEMC and Gemini Panels GEMC-12V2PS-R 12VDC

- Power Supply for Burg. Bus of GEMC Panels, remote supervised.
- Powered by supplied 16.5V, 50VA plug-in transformer,
- Supports 2ea. 12V, 7Ah standby batteries.
- Backward compatible with all standard Gemini Panels,
- Alarm Panel supervised power option

Note: Also available, Fire Bus Model with Direct 120VAC connection, model GEMC-12V2ASP-CF 12VDC



(Note: Housing is white in color, not as shown.)

Napco Commercial Access Control Option for GEMC and Gemini Panels

GEMC-ACM1D Access Control Module with power supply in enclosure **GEM-2D** 2nd Door Plug-In Module for use with ACM1D

Burglary & Fire Accessories & Options:

Wireless, UL Commercial, Peripherals

GEMC-REVC Wireless 255 point RF Receiver (4/system, max.)

GEMC-WL-SMK Wireless Smoke, Photoelectric

GEMC-WL-HEAT Wireless Heat, 135° F



GEMC-WL-WD Wireless 1-pt input module **GEMC-WL-WD2** Wireless 2-input module

GEMC-WL-PIR Wireless 50' PIR

GEMC-WL-DT Wireless 40' Dual Tech'y microwave/PIR

GEMC-WL-GB Wireless Glassbreak

Napco Commercial™ GEMC Combo. Fire/Burglary and Burglary Configurations and Components:

Commercial Fire & Burglary Accessories and Options

GEMC-BM/PS Burg Module with 12V power supply provides isolated 4-wire burg bus for burg keypads and devices, plus 12V power output for aux. devices. Independent Burg. Bell output. Complete separation of fire and burg power, plus indep. burg. battery connection and charger for indep. burg. standby operation in power failure.

GEMC-BM Burg Module, isolated 4-wire burg bus for burg keypads and devices, plus 12V power output for aux devices. Indep. Burg bell output.

GEMC-FW-SLC Addressable SLC Fire Module, supports up to 128 addressable SLC fire devices. Up to 2 connect to GEM-C panel.

GEMC-BSLC Addressable SLC Burg Module, supports up to 128 addressable SLC burg devices. Up to 2 connect to GEM-C panel.

GEMC-F8ZCPIM Conventional 8-zone 2-wire fire input module. Plugs into GEM-C panel, for conventional 2-wire smokes or any conventional fire detection device.

Burglary Peripherals

GEMC-BK1 LCD Burglary Keypad for Combo. System, with 4-zone EZM built in (Requires GEMC-BM or BM/PS Module.)

GEMC-BSLC-4PT Addressable SLC 4 point input expansion module

GEMC-BSLC-1PT Addressable SLC 1 point input expansion module

GEMC-BSLC-DT Addressable SLC Commercial Dual Tech Microwave/ PIR, $40\times40^{\circ}$

GEMC-BSLC-PIR Addressable SLC Commercial PIR, 50 x 50'

GEMC-BSLC-RLY Addressable SLC Commercial 1 point output module

GEMC-WL-PIR Gemini Commercial Wireless PIR, 50 x 50'

 $\textbf{GEMC-WL-GB} \; \text{Gemini Commercial Wireless Glassbreak, Acoustic } 25^{\prime}$

GEMC-WL-DT Gemini Commercial Wireless Dual Tech Microwave/PIR, $40 \times 40'$

Fire Peripherals

GEMC-FK1 LCD Fire Red Keypad

GEMC-WL-SMK Gemini Commercial Wireless Smoke, Photoelectric

 $\textbf{GEMC-WL-HEAT} \; \text{Gemini Commercial Wireless Heat, } 135^{\circ} \, \text{F}$

Common Peripherals - For Commercial Fire and/or Burglary Systems

GEMC-WL-WD Gemini Comml Wireless slim profile 1-input wireless module

GEMC-WL-WD2 Gemini Comml Wireless 2-input module converts any UL listed device into a UL wireless device (ex., pull stations or sprinkler supervisories.)

GEMC-REVC Gemini Commercial Wireless 255 point RF Receiver (up to 4 per system, max.)

GEMC-EZM8 8-point expansion module

GEMC- FPRINT Parallel printer module

GEMC-RM3008 8 Form C Relay Output Module

GEMC-NL-MOD Internet Reporting Module

GEMC-RS232 RS232 Adapter for serial output from GEMC Panel

GEMC-OUT8 PGM Output Module, 8 open collector PGM outputs

GEMC-KOTamperKT Merchantile Tamper Kit, for large panel enclosures, supervised. (Not necessary if housing is recess-mounted.)

Firewolf Addressable Peripherals

FWC-FSLC-SMK Addressable Analog SLC Smoke, photoelectric, head**

FWC-FSLC-HEAT Addressable Analog SLC Heat, 135°F, head**

FWC-FSLC-DUCT Addressable SLC Duct smoke detector, photoelectric **FWC-FSLC-DUCTRA** Remote Indicator Plate with LED indicator & key

FWC-FSLC-EZM2 Addressable SLC 2-zone conventional expansion module. Uses one address on SLC loop, but yields 2 indepent contact monitoring circuits, for pull stations, water flow and other dry contact alarm initiating devices.

FWC-FSLC-EZM1 Addressable SLC 1-input conventional module, similar to usage above.

FWC-FSLC-CZM Addressable SLC single module, for montoring of dry contacts, ie., pull stations and conv. smokes

FWC-FSLC-RM2 Addressable SLC 2-output module (requires 1 SLC address)

FWC-FSLC-ISO Addressable SLC Short Circuit Module. (Optional use, for certain apps. only; meets Class A, Style 7 loop reqts.)

FWC-FSLC-SOM1 Addressable SLC Fire supervised output module. Application examples: elevator recall, HVAC shutdown, add'l NAC output with power supply

FWC-FSLC-PULL Addressable SLC Fire Pull Station

FWC-FSLC-PULLK Addressable SLC Pull Station, key reset

FWC-FSLC-PULL2 Addressable Dual Action Pull Station

FWC-FSLC-PULL2K Addressable Dual Action Pull Station, Key Reset

FWC-FSLC-PROG2 Tool for address-programming SLC devices

 $\begin{tabular}{ll} FWC-FSLC-SMK6B ** Smoke/Heat 6" Base, required for FWC-FSLC-SMK and -HEAT devices \\ \end{tabular}$

Options

GEMC-12V2APS-CF 12VDC Power Supply for Fire Bus, remote supervised. Direct 120VAC connection, supports 2ea. 12V, 7Ah standby batteries.

GEMC-12V2APS-R 12VDC Power Supply for Burg. Bus, remote supervised. Powered by supplied 16.5V, 50VA plug-in transformer, supports 2ea. 12V, 7AH standby batteries.

GEMC-NAC6 Remote 4-output NAC Extender, for 6.5A ttl, or 2A, max. on any 1 output. Red 14 x 16" can, connects to 120VAC, supports 32Ah standby batts. Supervised, fire bus connection. System Sensor and Wheelock NAC synch. (5 per system, for 20 add'l NAC circuits total.)


GEM-ACM1D Access Control Module (with power supply, provision for back up battery, in enclosure, plug-in transformer), 1 door kit

GEM-2D Access Add-on 2 door plug-in PCB for expansion of door capacity in above.

Napco Commercial GEMC Fire & Burglary Configuration Diagram

NAPCO I COMMERCIAL

Platform supports commercial analog, addressable, wireless or conventional fire or burglary devices.




2 SLC MODULES, max.

- Two Fire or
- Two Burglary or
- One Fire and one Burglary
 Note: The four GEMC-RECV max. is reduced by 1 for each SLC module.

[†]Residential Burglary when both loops are used Single Commercial Burglary Supervised Loop and Integral Magnetic Contact

Napco Commercial GEMC Fire & Burglary Configuration Diagram

FIRE BUS DEVICES



MAPCO I COMMERCIAL

Napco Firewolf™ Analog Addressable 24V Fire Systems for 32 to 255 points:

Napco Commercial Firewolf™ Intelligent features, cost-effective design and up-to-the-minute, regulatory compliance for life safety from 32 to 255 points

Features:

- Analog, Addressable, Conventional, Wireless &/or Hardwired technologies
- Wireless Fire Full line of UL Commercial Grade long-range supervised models
- More Addressable Devices than any in its class; mile-long loop and more device load ea.
- ✓ Code-compliant integrated Security System option with independent pre-isolated circuits
- More value and power on-board for a more cost-effective solution -✔ Built in DACT (TCP/IP option), Horn/Strobe Synch Module (Wheelock/System Sensor protocol), 4 NACs (up to 24), 7A power, regulated 24V output
- ✓ Cost-effective retrofits -supports conventional legacy devices & existing wiring (all types/gauges)
- Comprehensive local and remote programming & diagnostics. Printable AHJ reports of analog device sensitivity settings with current readings (uploadable)
- Optional NAC Extender for universal FACP support and Regulated Power Supplies, too
- Compliances NFPA 72, UL Commercial Fire, UL864 9th Ed., UL985, CSFM and NYC Fire Department Certifications.

Napco Commercial Firewolf 255pt 24V Intelligent



Addressable Commercial Fire System Kit **GEMC-FW-255KT**

- 24V Panel, 255 pts via commercial addressable, wireless or conventional fire devices, 4 on onboard NACs providing up to 6.5A notification power
- 7Amp, 24V Power Supply
- Built in horn strobe synch module on each NAC (Wheelock/System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports; optional
- Quickloader up/downloading incldg remote smoke sensitivity report and settings by device; Automatic drift compensation for smoke
- Nearly a mile max. wiring run any wire type ideal for retrofits. 24V and 12V legacy devices supported
- Large red locking enclosure, flush or surface mount. Up to 32AH battery capacity.
- Includes Fire Keypad (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus

Napco Commercial Firewolf 128pt 24V Intelligent Addressable Commercial Fire System Kit

- 24V Panel, 128 pts via commercial addressable, wireless or conventional fire devices, 4 on onboard NACs providing up to 6.5A notification power.
- 7Amp, 24V Power Supply
- Built in horn strobe synch module on ea. NAC (Wheelock/System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports; optional
- Quickloader up/downloading including remote smoke sensitivity report and settings by device; Automatic drift compensation for smoke detectors too
- Nearly a mile max. wiring run any wire type ideal for retrofits.
- Supports 24V and legacy 12V devices
- Large red locking enclosure, flush or surface mount. Up to 32AH battery capacity
- Includes Fire Keypad (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus (Also, full keyswitch support.)



Napco Commercial Firewolf 32pt 24V Intelligent Addressable Commercial Fire System Kit **GEMC-FW-32KT**

- 24V Panel, 32 pts via commercial addressable, wireless or conventional fire devices, 2 on onboard NACs providing up to 4A notification power.
- Locking medium red enclosure (flush or surface mount). Houses up to 16AH battery backup.
- 7Amp, 24V Power Supply
- Built in horn strobe synch module on ea. NAC (Wheelock/System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports; optional
- Quickloader up/downloading incldg remote smoke sensitivity report and settings by device; Automatic drift compensation for smoke detectors too
- Nearly a mile max. wiring run any wire type ideal for retrofits. 24V and 12V legacy devices supported.
- Includes Fire Keypad (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus (Also, full keyswitch support.)



Napco Commercial Firewolf 32pt Conventional Fire System Kit - Ideal for sprinkler/waterflow

GEMC-FW32CONVKT

- 24V Panel, 32 Points via commercial addressable, wireless or conventional fire devices, 2 onboard NACs providing up to 4A notification power
- Locking, Medium Red Enclosure, 16 x 17" door, with 14.25" x 16" base (flush or surface mount). Houses up to 16Ah battery backup.
- 4 Amp, 24V Power Supply
- Conventional 8-zone 2-wire fire input module, for conventional 2-wire smokes or any conventional fire detection device (GEMC-F8ZCPIM)
- Built in horn/strobe synch. module on each NAC (Wheelock/System) Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading
- Menu-driven LCD Fire Keypad mounts anywhere on bus (GEMC-FK1)

7Amp NAC Extender for Universal FACP use or with GEMC / Firewolf Systems **GEMC-NAC7S**

- 7 Amps of Power for use with NAPCO or other FACP panel brands
- 4 onboard NACs with up to 2A ea. expandable for up to 24 per system
- Regulates 24V auxiliary power
- Distributes synched bell and strobe outputs with built-in module
- Monitors AC, battery trouble, tamper and ground fault on Napco bus or provides universal FACP support
- Red locking enclosure, accommodates up to 16Ah total battery capacity

12VDC Fire Power Supply for GEMC / Firewolf and Gemini Panels

GEMC-12V2ASP-CF 12VDC

- Power Supply for Fire Bus of GEMC Panels, remote supervised
- Direct 120VAC connection
- Supports 2ea. 12V,7Ah standby batteries

Wireless, UL Commercial, Fire Peripherals

GEMC-REVC Wireless 255 point RF Receiver (4/system, max.) **GEMC-WL-SMK** Wireless Smoke, Photoelectric (complete)

GEMC-WL-HEAT Wireless Heat, 135° F

GEMC-WL-WD Wireless 1-pt input module


GEMC-WL-WD2 Wireless 2-input module (converts any UL device into a wireless device, ex. pull stations or sprinkler supervisories.)








FIREWOLF SYSTEM COMPONENTS





Addressable Fire Peripherals

GEMC-FW-SLC Addressable SLC Fire Module, supports up to 128 addressable SLC fire devices, below. (Connect up to 2/panel.)
FWC-FSLC-SMK Addressable Analog Smoke Photoelectric, head**
FWC-FSLC-HEAT Addressable Analog Heat, 135 degrees, head**
FWC-FSLC-DUCT Addressable Duct smoke detector, photoelectric.
FWC-FSLC-DUCTRA Remote Indicator Plate with LED indicator & key reset

FWC-FSLC-EZM1 Addressable SLC 1-input conventional module, similar usage to above.

FWC-FSLC-EZM2 Addressable 2-zone conventional expansion module. Uses one address on SLC loop, but yields 2 independent contact monitoring circuits for pull stations, waterflow and other dry contact alarm initiating devices.

FWC-FSLC-CZM Addressable single module, for dry contacts **FWC-FSLC-RM2** Addressable 2-output module (uses 1 SLC address) **FWC-FSLC-ISO** Addressable Short Circuit module (Optional for special apps., meets Class A, Style 7 loop reqts.)

FWC-FSLC-SOM1 Addressable Fire supervised output module (ex. Elevator recall, HVAC shutdown, additional

FWC-FSLC-PULL Addressable Pull Station

FWC-FSLC-PULLK Addressable Pull Station, Key Reset FWC-FSLC-PULL2 Addressable Dual Action Pull Station FWC-FSLC-PULL2K Addressable Dual Action Pull Station, Key Reset FWC-FSLC-PROG2 Tool for address programming SLC devices FWC-FSLC-SMK6B **Smoke/Heat, 6" base required for FWC-FSLC-SMK & -HEAT

Conventional Fire Peripherals

GEMC-FK1 LCD Fire Red Keypad (Menu-driven operation, functionality for Reset, Acknowledge, Silence (with disable).

GEMC-F8ZCPIM Conventional 8-zone 2-wire fire input mod.

GEMC-EZM8 8-pt expander

GEMC-NL-MOD Internet Reporting Module

Output Options for Fire Systems

GEMC- FPRINT Parallel printer module GEMC-RM3008 8 Form C Relay Output Mod GEMC-RS232 RS232 Adapter for serial output GEMC-OUT8 PGM 8-Output Module

Firewolf Conventional Fire/Life Safety Devices



Advanced photoelectric smoke detectors

Proven to more accurately detect a wide range of fire types and to reliably, outperform conventional photoelectric detectors. Detects virtually all types of fires including paper, wood, gasoline, polystyrene, and smoldering fires.

FW-2 2-Wire FW-4 4-Wire

- Low Profile
- RF/Transient Protection
- Two built-in power/sensitivitesupervision/alarm LEDs
- Non-directional smoke chamber
- Vandal resistant security locking feature
- Removable smoke labyrinth for cleaning or replacement

FW2H Also available with Heat Sensor

 With built-in thermal heat sensor for more fire codes requiring 135°F fixed



More sound in fire...

Firewolf 2-Wire Smoke Detectors with built-in 85db sounder and Line Reversal Module

FW2S Smoke Detector with built-in sounder **FW-RM1** Reversal Module



Advanced photoelectric smoke with built-in thermal heat detector

FW2-H 2-Wire with heat, FW4-H 4-Wire with heat

Same features as FW-2 & FW-4 plus -

Built-in thermal heat sensor for more fire codes requiring 135°F fixed.



Firewolf 12/24VDC carbon monoxide detectors

FW-CO12 12VDC

FW-CO1224 12/24VDC (selectable)

- Designed for professional residential & commercial alarm systems
- UL2075 Listed. Tested to meet UL2034 CO response requirement
- 12 to 24VDC for varied applications
- Attractive compact styling (under 5") and neutral color for every décor
- Precise solid state infrared sensor technology & smart microprocessor optimize life safety & detection accuracy
- Patented technology: Simulates CO gas level response in human blood stream
- Independent lab tests prove superior false alarm immunity over electrochemical units (Lawrence Berkeley National Laboratory #40566)
- Powerful 85db alarm sounder & LED
- Easy Test/ Silence-Reset button



Conventional single action, dual action & key-reset pull stations

FW-PULL1

- Non-coded single or double action devices which initiate an alarm when pulled.
- Resetting of the FW-PULL1 is accomplished by inserting a small screwdriver
- Durable extruded aluminum construction and finished in red
- Pull stations can be converted to dual action with the addition of the FW-PULL2MOD double action lever kit
- Key reset version also available FW-PULL1K

iBridge Remote Services

The new way to grow your business in any economy (and prevent attrition)



Who wouldn't pay to be in 2 places at once?

Today, we all lead highly-connected busy lives on the go, with countless people, places and things to check on and control.

Napco's been delivering affordable mobile security services for you to provide accounts all along (longer than anyone else). There's iSee Video, for RMR from hi-res streaming IP video with video-alerts; installed WiFi, inside or out. And, our iRemote Keypad provides total system control, identical to the real keypad, right down to address programming, plus apps for Blackberry, Droid and iPhones & iPads. Now, we've integrated it all for online control or on Napco's new Droid-based Touchscreen/Tablet. Plus, we're adding Z-Wave™ Lighting and Temperature Control. We call it iBridge. You'll call it new RMR.

Napco's iBridge Integrated Remote Security Service is the singular solution for your customers, and for you to continue to grow your business. It'll help your new and existing accounts stay, in the loop and in control of their lives; alarm and video cameras, plus lighting and HVAC, from virtually anywhere in the world, from any PC, tablet computer or smartphone.

iBridge... Guaranteed to be of real comfort and value to accounts, even in this economy, and an innovative new way for you to earn incremental recurring revenue while elevating your system offering, customer service and account retention.

New! Napco iBridge Interactive Remote Services . . .

i Bridge®





Napco iBridge Touchscreen Keypad & Tablet Computer

IBR-TAB

- Portable 7" Tablet -Touchscreen computer with 802.11 WiFi wireless technology
- Touchscreen control of security system and more, from anywhere in the home/business (up to 100' range). Operate keypad, see video cameras inside and out and control climate & lighting.
- Easy on/off magnetic docking frame, doubles as a wall mount and charging station.
- Portable, lightweight, slim design, less than ½"
- Android[™] operating system; Google[™] internet browser-enabled
- Handy on-screen tools: Message Minder (recordable voice messages with playback); weather, calculator, etc.
- Full color, hi-resolution display (800 x 480)

- Choice of Keypad Modes: Conventional Gemini and highsecurity "Scramble Button" thwarts onlookers
- Alarm Integration: Full keypad control and functionality (identical to iRemote), Displays system status messages, zone descriptions, etc. Visual and audible "system trouble" messages. Touchscreen function F, P, A panic buttons
- Video Integration: Live video, camera-viewing and integrated use with iSee Video Cameras (quad view or individual cameras)
- Lighting & Climate Integration, using Z-Wave IBridge Devices. Lighting & thermostat control and scheduling with easy to set touchscreen controls (right)
- High-speed, powerful processor
- Tabletop stand/dock also available (IBR-ITABSTAND).
- Works with IBR Panel Interface (shown, supplied in IBR-ITABKIT)
- i Bridge Touchscreen and Z-Wave Interface with all Gemini Panels P800 to X255 plus GEM-C.

Touchscreen Tablet, Virtual Keypad, Home Controls & Integrated iSee Video











in complete IBR-ITABKİT



iBridge Lighting & Climate Integration with Z-Wave Devices

Napco's iBridge integrated mobile services suite includes interactive remote temperature and lighting control accessible from any online computer, tablet smart device, smartphone or the iBridge Tablet Touchscreen, using the iBridge app. and the growing number of available Z-Wave™ Devices that are simply plugged into iBridge's own Z-Wave Controller Module (IBR-ZWAVE) and enrolled on the iBridge wireless network in true plug-n-play fashion.

Seamlessly integrated with the other iBridge functions and the Napco System, your accounts' premises' lights and climate can be reviewed, reset or remotely controlled on-the-fly conveniently and easily right on their smartphone, for example; and/or custom scheduled, setup to automatically save home- and small-business energy costs and by maximizing the efficiency of their use of electrical appliances & heating and cooling systems, whether they're there or away.

Growing in both popularity and models, literally from hundreds of manufacturers, today z-wave devices are available for controlling anything that uses electricity, including lighting, thermostat and electrical appliance modules (as shown) and more.

Z-Wave is a wireless mesh networking technology that enables each device to send and receive data wirelessly, so it can be controlled /automated in real-time. Easily installed -- there are no cables to run or complex programming, z-wave devices can be put virtually anywhere and added anytime. Plus, Z-wave RF technology does not interfere with WiFi networking, and does not require a neutral ground be present (i.e, in older homes).

IBRIDGE ORDERING

IBR-ITABKIT Complete Kit, iBridge Touchscreen Tablet w/ frame/charger plus Wireless Panel Interface. (Interface supports 4 IBR-ITAB Touchscreens).

IBR-ITAB iBridge Touchscreen Tablet with mounting frame/charging dock

IBR-ITABSTAND Angled tabletop stand/docking station, ideal for bedrooms, kitchens, desks, etc.

IBR-WIFI-MOD Wireless Panel Interface, communicates between internet, Gemini Panel and IBR-TAB Touchscreen Tablet.

IBR-ZWAVE iBridge Z-Wave Controller for integrated control of Z-Wave technology devices. (not shown)

Gemini Remote Virtual Keypad:

Easy online system control on-the-go.

iRemote



IREMOTEMOD/12


- Remote keypad access anywhere, works & looks like any Gemini keypad model.
- Supports all Gemini model panels and keypads
- Remote control Gemini Virtual Keypad with Free 12-months account access on Free custom dealer web site
- \blacksquare Simply wire iRemote[™] Module on the panel's keypad bus.
- Exactly mirrors keypad on premises for easy 24-7 control via web and PC or smartphone
- 100% full-function "keypad" for easy remote troubleshooting without making a service call

- Bonus functionality Up/download to panels via internet in just seconds; alarm reporting to central station via internet
- Free downloadable apps for iPhone/iPad, Blackberry, Android
- Panel Compatibility GEM-X255, GEM-P9600, GEM-P3200, GEM-P1664, GEM-P1632, GEM-P816

ORDERING:

- iRemoteMod/12 Module with 12 months subscriber access, included
- **iRemote64Pak** with GEMP1664 4-Area Panel, Talking GEMK1VPS Keypad and transformer, and iRemoteMod/12.

WIRING OF IREMOTE MODULE ON KEYPAD BUS



Tens of Thousands of Accounts & Growing Strong

iSeeVideo NAPCO



iSee Video™: Affordable Professional Quality Hi Res Remote Video pioneered by Napco...

Napco pioneered remote video and today's iSee Video is the reliable, easy-to-install, ideal upsell solution for residential and smaller commercial accounts alike. It's the affordable remote video service accounts want, where kids, pets, elders or employees, boats or vacation homes are viewable on any PC or smartphone anywhere, 24/7. They'll view live streaming video, archived or emailed events from a supplied secure multilingual website we provide, that security companies can customize with their logo, phone, URL and contact info. It can be deployed with any of three indoor or outdoor iSee Video 802.11 WiFi Camera, with a secure-networked installation in as little as 10 minutes, or you can use your choice of ana-

log camera brand, instantly converted to IP cameras with our Video Gateway. Both methods give you and your residential or commercial customers the high-res. professional quality iSee Video online remote video service you'd expect from Napco.

And, now iSee Video is a featured application integrated in the iBridge suite of interactive online services, including the iBridge Keypad Touchscreen/Tablet Computer.

(see page 11)



iSeeVideo: Our Camera or Yours . . .



WiFi, Hi-Res., streaming video, viewed 24/7 on-the-fly or capturing an event, sent to client's smartphone or computer online, anywhere.

Fast installs with WiFi indoor/outdoor cameras that auto-enroll and secure-lock their video network. Hires full-frame viewing, and fastest frame rate for live streaming video – not herky-jerky little screens that can't be blown up.

WiFi Camera Features

- Put video accounts online in as little as 10 minutes
- Upsell your residential and small business alarm accounts on very affordable video for incremental RMR
- Highest resolution remote video on the market! 20 frames per second @ VGA res. (640x480)
- 802.11 cameras easily enroll on network with patented wireless access point's auto-detect mode (All wireless cameras have a hardwire jack option too.)
- Free Apps. iPhone/iPad, Blackberry, Droid.
- Professional quality -View online in quad screen configuration or by-camera, Quickly review archived video with film-strip style thumbnails with time/date-stamp
- Choice of Wi-Fi Cameras, pan & tilt, outdoor/waterproof or fixed IP, in all-inclusive turnkey kits, include one year of subscriber service. And soon, new Megapixel Camera with IR and built in PIR.

Our Camera or Yours...

Put any analog camera of any brand online easily with iSee Video remote service using the **Single Channel Gateway, model ISEE-SCHGW/12**, that instantly converts any analog CCTV camera into a high-res. internet-ready IP camera online (use up to 6 per account). Streaming or stored video can then be remotely accessed anywhere in the world, 24/7, from any web-enabled computer or smartphone with Free Apps. for iPhone/iPad, Blackberry, Droid. Plus using optional alarm system input triggers, video can be automatically captured and/or emailed to accounts upon alarm events, such as business opens/closes, returning children (disarm), retiring of elder parent (arm), departure of staff (cleaning people or service contractors).



gle Channel Gateway Customize iS

Customize iSee Video for your accounts to see your company logo & contact info. (Free)

Single Channel Gateway Features

- Simply plug the CAT5 cable into premises' router and the camera will automatically adapt to the network regardless of service and modem type. Even in the most inflexible corporate networks, the video camera will auto-configure through the network to iSee Video's www.videoalert.net server.
- Professional widescreen VGA, high-res. video images of 704 x 480, max.using MPEG4 compression
- Fast 20FPS video viewing on the Napco-provided server including 12-months subscriber access to 50MB of video storage. Or, for full-time recording, use the affordable iSee Video Internet Video Recorder (IVR250, below).
- View online in quad screen configuration or by-camera, Quickly look-up archived video with film-strip style thumbnails with time/date-stamp
- -or- advanced pixel-based motion detection on demand or on event, can transmit video clips to the www.videoalert. net server and/or provide a "video alert" to the account
- Local TV viewing option Gateway provides a local video output for optional signal for BNC video-in/-out connection to a monitor, or for local distribution, using a video modulator. –Great for viewing outdoor cameras while clients remain safe & comfortable inside.
- Free Dynamic IP support

ISEE-IVR-250: Record up to 30 days of continuous video - playback and control online.

IVR250

iSee Video Internet Video Recorder for Full-Time Recording

- Continuously record and store up to 30 days of video from up to six iSee Video System cameras with our new Internet video recorder (ISEE-IVR250)
- Record high resolution video, with continuous recording of up to four cameras at 20 FPS. Add two more with virtually no loss of image quality thanks to Dynamic Image Reduction
- Easy retrieval and viewing by the online subscriber from password protected online interface which offers userfriendly navigation aids, quick-review/locate/calendarlookup tools, time-/date-stamped video and an easy-to-use file-export utility.

- Dually supervised; plug and play setup no software to load or configure
- Safely stores video on iSee Video server, provided. Easy, secure internet access, retrieval and video look-up
- Provide more reliable video recording and get monthly RMR instead on a one-time DVR hardware sale!









ISEE VIDEO ORDERING

ISVWLKIT1 Complete Wireless Camera Kit: One (1) 802.11 Wireless Fixed Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website login screen and 12-months iSee Video Network access. (Kits support up to 6 cameras).

ISVWLPTKIT2 Complete Wireless P/T Camera Kit: Kit as above but with one (1) 802.11 Wireless Pan/Tilt Camera, 640x480 hi-res.

ISVWLOKIT3 Complete Wireless Outdoor Camera Kit: Kit as above but with one (1) 802.11 Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vison filter, power adapter.

ISVWLHDKIT4 Complete Wireless Megapixel Camera Kit: Kit as above but with one (1) 802.11n Wireless HD Megapixel Camera,: 720p HD (1280x720), Infrared (IR), built in PIR (3.8"H x 2.5"W x 1.4"D (plus base, approx 3"sq.); power adapter.

ISVWLCAM Add-on 802.11 Wireless Fixed Camera: 640x480 hi-res AC transformer. Includes 12-months iSee Video Network access. For Hardwire-Only version order ISEE-VCAM1/12

ISVWLCAMPT Add-on 802.11 Wireless Pan/Tilt Camera:

640x480 hi-res, power adapter. Includes 12-months iSee Video Network access. For Hardwire-Only version order ISEE-VCMPT/12

ISVWLOCAM Add-on Wireless Outdoor 802.11 Camera:


Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR, 6 IR LEDs with photo cell activation and night vison filter, power adapter. Includes 12-months iSee Video Network access.


ISVWLHDCAM Add-on 802.11 Wireless HD Megapixel Camera with Infrared (IR) and built in PIR: 720p HD (1280x720), IR, PIR, AC transformer. Includes 12-months iSee Video Network access.

ISEE-SCHGW/12 Single Channel Gateway for more conventional CAT5 or Coax Installations: (1) ISEE-SCHGW widescreen. VGA Res (704 x 480) at up to 30 FPS, MPEG4 compression, audio mic input and speaker output. Includes 12-months iSee Video Network access.

ISEE-IVR250 Optional - Internet Video Recorder: Provides full-time hi-res recording of up to 6 cameras for 30 days (640x480).

iSeeVideo is Easy!







FROM NAPCO THE LEADER IN REMOTE VIDEO SERVICES

Gemini Keypads: Selection, ease of use & seamless compatibility



Custom alphanumeric keypads

GEMK1CA and GEMRP1CAe2

- Deluxe 32-character backlit, menu-driven, dual-line display
- Custom alphanumeric zone directory
- Built-in 4 Zone expansion module
- Display of wireless transmitter signal strength 1-10
- EZ Keypad Programming2 with actual Q&A's
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant (hold-down) with the GEMK1CA. Traditional interior and instant keys with the GEMRP1CAe2
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength indication
- Fire, police and auxiliary programmable panic keys
- Fingertip reference chart



Alpha/symbol keypads

GEMK2AS and GEMRP2ASe2

- Unique backlit, combination alphanumeric and symbol display
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant key (hold-down) with the GEMK2AS. Traditional interior and instant keys with GEMRP2ASe2
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys
- Fingertip reference chart



Talking, Multifunction Keypad with voice assist, UL siren & pet PIR built in

GEM-K1VPS

- For use with GEMP1664 and GEMP1632 Panels, for 64 or 32 user codes, each
- Talking voice prompts (adjustable volume)
- Large blue custom alpha display
- Built-in 88db burg/fire alarm siren (temporary hush mode)
- Built-in wide-angle 25' pet PIR and smart occupancy sensor
- Supports event log viewing
- Optional temperature display (with GEM-TEMP64 module) (see Gemini

Accessories pg. 21)



Pick your keypad; Your way

GEMINI PANELS



iRemote Virtual Keypad and iBridge Touchscreen/Tablet pages 13 and 11 respectively.







K-Series: Intuitive, stay & away ease-of-use



RP Series: Traditional interior and instant keys





Door style keypads

GEM-DK1CA

- Contemporary, pure black and white styling
- Door covers keys for cleaner lines & prevents unwarranted use
- Bright blue backlit custom LCD display & alphanumeric zone directory
- Blue backlit keys brighten to the touch and feature easy stay and away functionality
- Built in 4-zone expander
- 3 built in panic buttons
- Familiar Napco operation, identical usage and programming to GEM-K1CAe2
- Distinctive new look distinguishes dealers from competitive alarm companies

(Also available in digital model GEM-DK3DGTL, shown right)



Keypad with built in wireless 32 pt. Gemini RF receiver

GEMK4RF

- Built-in 32 Point Gemini wireless receiver for labor-saving convenience
- Large backlit, fixed English display
- Proven crystal-control wireless performance
- Supports all Gemini transmitters
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy "instant" (hold-down)
- Large soft touch backlit keys with tone
- Wireless transmitter signal strength indication
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys
- Matching keypad without-receiver GEMK4



Digital keypads

GEMK3DGTL and GEMRP3DGTL

Vivid dual 7-segment digital display keypad

- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant (hold-down) with the GEMK3DGTL Traditional interior and instant keys with the GEMRP3DGTL
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength indication
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys



800-Series' classic custom alphanumeric keypad with stay & away keys

GEMRP8LCD

- Deluxe 32-character backlit dual-line custom alpha display & directory
- Built-in 2 zone expansion module
- Display of wireless transmitter signal strength
- EZ Keypad Programming2 with actual Q&A's to step through configuration
- New intuitive, stay & away ease-of-use buttons, for easy one button arm and easy "instant" (hold-down)



GEM-K800 and GEM-RP8 numeric LED keypads

- Backlit keys and vivid red LED numeric display
- Traditional-key styleGEM-RP8 supplied with GEMP801/P800
- Stay & Away version GEM-K800 available



Express LED/Door Keypads (for Express panels only)

RP-X6 & RP-X4

- Door-styling, conceals keys Backlit keys and
- Multilingual , vivid LED symbol & numeric display
- RPX-6 supplied with XP600; RPX-4, with XP400



Gemini BioReader Outdoor Digital / Fingerprint Keypad

GEM-BIOREADER/MS

- Indoor/outdoor digital keypad with a highly-advanced and accurate optical biometric fingerprint reader for integrated control of any Gemini security system or as state-of-the-art standalone access control use for alarm systems, garage door operator control, lighting, etc. with relay activation.
- Increases the security of the system Biometric ambush feature sends silent alarms. Use pre-selected and enrolled finger to silently call the police during push ins and robberies
- Convenient for consumers- No keys or cards to carry, no codes to memorize and remember



- Eliminates code pass-along. With children or employee-turnover - you can't pass along a fingerprint!
- Users. System supports 100 biometric fingerprints, that can be mapped to Panel User Codes for logging who armed/ disarmed.
- Supervised (e.g., reports if unit is ripped from building)
- Duable metallic silver powder-coat finish.

Residential applications Keyless use ideal for children; Memory-free for elderly; Easy Residential alarm and garage door control.

Commercial applications such as gate control and parking lot access; restricted access to sensitive pharmaceuticals, weapons, supplies and more.



Expandable Gemini hybrid controls feature:

- Wide choice of designer keypads for every application and budget (see p. 19)
- Use new iBridge Keypad Touchscreen/ Tablet for integrated security, climate, lighting or video control or iRemote Virtual Keypad (for smartphone or computer remote interface) in place of any custom alpha keypad
- Up/downloading, including unique PC-preset unattended method with PCD-WINDOWS
- EZ-Programming mode at keypad
- Choice of Gemini RF receivers & transmitters
- Multi-stage lightning protection
- Event log with open/closes suppression
- Telco line cut supervision
- Fuseless, maintenance-free operation
- Support all major communication formats plus internet & StarLink GSM Radio up/downloadable, primary or backup communicator
- Transformer, supplied

Gemini X255 is the expansive hardwire/ wireless control offering 255 fully-programmable zones, 195 users, fuseless operation & supports the full line of top performing Gemini Wireless

Features:

- 8 to 255 hardwired zones or wireless zones/pts
- Expandable using 8-zone GEM-EZM8 expansion modules
- Up to 96 fire zones, with 8 2-wire fire zones
- Up to 8 areas
- Up to 195 user codes with open/close by user
- 3 On-board relay output & 1 prog. lug
- Up to 96 relays
- Supports 4 wireless receivers
- Supports 15 GEMRP1CAE2 or K1CA keypads
- Up to 2 interior bypass groups
- 800 Event log w/ open/close suppress
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

Gemini P9600 powerful multi-tasking hybrid control panel – feature-rich for security applications and home automation integration

Features:

- 8 to 96 hardwire zones/points
- Including 8 2-wire fire zones
- Up to 96 user codes
- Up to 8 areas
- 3 On-board relay outputs; expandable to 96
- 1 On-board programmable lug
- Up to 4 RF receivers
- Up to 15 keypads
- Up to 2 interior bypass groups
- 800 Event log
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

Gemini P3200, a popular, all-around 8 zone hybrid control expandable to 32 zones or 48 wireless points

Features:

- 8 to 32 hardwire or wireless zones/ points;
 up to 48 RF wireless points
- Including 2 2-wire fire zones

virtual keypad, touchscreen/tablet, internet- & GSM-communications.

- Up to 48 user codes
- Up to 2 areas
- Fuseless, maintenance-free operation
- 3 On-board relay outputs; expandable to 24
- 1 On-board programmable lug
- Up to 2 RF receivers
- Up to 7 keypads
- Interior bypass groups
- 800 Event log
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

Gemini P1664, 4-area hybrid panel with 8-64-zones of power; supports all keypads plus talking multifunction keypads with built in siren & pet PIR

- 8 to 64 hardwire or wireless zones
- Up to 64 fire zones, with 2, 2-wire fire
- Up to 64 user codes
- Up to 4 areas
- 400 event log; viewable at custom alpha keypads
- Up to 2 RF receivers
- EZ Programming at keypad and Auto Arm
- Supports up to 7 keypads: all standard Gemini Keypads and/or talking, multifunction GEM-K1VPS (may be intermixed)
- Supports 3 outputs; expandable up to 16 external outputs (RB/RM3008)
- 2 PGM outputs
- 1 interior zone group; 2 prog. chimes by zone;
- SIA CP01 features

Gemini P1632, ultra-popular hardwire/wireless control panel with partitioning – easy to standardize for both residential & light commercial applications

Features:

- 8 to 32 hardwire zones/points
- Including 2 2-wire fire zones (7;8)
- EZ programming at keypad
- Up to 32 user codes
- Up to 2 areas
- Supports up to 7 keypads and/or talking, multifunction GEM-K1VPS (may be intermixed)
- 3 On-board relay outputs; expandable to 8 relay outputs
- Up to 2 RF receivers
- Interior bypass groups
- 400 Event log
- Auto arm

Gemini P816, an economical hardwire/wireless control panel that works seamlessly with all standard Gemini keypads and wireless

Features:

- 8 to 16 hardwire zones/points
- Including 2 2-wire fire zones
- Up to 16 user codes
- Supports up to 7 keypads
- EZ Programming at keypad
- 256 event logging
- Supports 2 Gemini receivers
- Interior bypass group
- Auto arm
- 3 Outputs

Gemini P801, economical 9 zone hybrid with your choice of numeric or custom alpha keypads

Features:

- 9 Programmable zones: 6 Hardwire or wireless zones plus 2 wireless zones plus 2-wire fire zone
- Use 2 optional zones at GEMRP8LCD custom alpha keypad
- For Control packed with RP8LCD Custom Alpha Keypad, order GEM-P801ALPHA
- For control packed with RP8 Numeric LED Keypad, order GEM-P801
- Uses GEMRECVXP8 wireless receiver
- 8 Individually reporting user codes
- 50 Event log
- Line and bell-cut supervision
- Double reporting & backup reporting
- EZ wire full-size terminal strips

Gemini P800, ultra-affordable hybrid control includes numeric keypad and 6 zones plus fire and panic

Features

- 8 programmable zones, including 2-wire fire zones
- Up to 16 Gemini wireless points: 8 wireless points from your choice of Gemini PIR, window/door & glassbreaks
- Up to 4 Gemini wireless smoke detectors and 4 GEMKEYF fobs
- 8 individually reporting user codes
- Supports up to 4 GEM-RP8 keypads &/or 2 wireless receivers (GEM-RECVXP8)
- Supports GEM-R8LCD/K800 Custom Alpha Keypad
- Includes control, Numeric LED Keypad and transformer

Gemini Accessories

GEM-EZM4/8 Expansion Module

 Economy 4 to 8 zone expansion module supports GEM-P816, GEM-P1632 & GEM-P1664

GEM-EZM8 Expansion Module

 Eight-zone expansion module (for all expandable GEM panels. Audible find mode)

GEM-PRINT

- Module that enables Gemini system activity to print to an on-site parallel printer
- For use with GEMP816 to X255 Controls

GEM-TEMP64

Indoor/Outdoor Temperature Sensor

provides Temperature Display at any Gemini Alphanumeric Keypad in a GEMP1632 and GEMP1664 System. Keypad will show Temperature in display, from -30 to 60C or -22 to 140F (replacing "Date" on keypad-display), e.g., GEMK1VPS, GEM-DK1CA, GEM-K1CA, GEM-RP1CAe2. Module is mounted inside or outdoors, to display either the temperature outside or inside room temperature. Tip: If used with IREMOTEMOD Module (below), the virtual keypad shown on the consumer's iPhone or laptop includes that temperature. Example, in a remote vacation home or hunting cabin, the unit can be mounted inside so endusers can check in remotely from anywhere, and make sure the room temp. is sufficient, preventing frozen/burst pipes etc., likewise knowing if and when an HVAC system fails, can help prevent damage/molds in heat.

IREMOTEMOD/12

Gemini Virtual Keypad module provides a mirror-image, fully-functional, remote control keypad on a on any PC or smartphone online anywhere in the world (free apps for Blackberry, iPhone/iPad, Droid). Module simulates real keypad model at physical premises and simply wires on GEM-Panel's keypad bus. (see page 13)

IBR-TAB

iBridge Touchscreen/Tablet Keypad/Video/ Automation/Web Interface. For GEM Panels, X255 thru P816 (see page 11).

Express Systems with multilingual LED XP keypads

XP400WK, XP600WK, respectively

- Feature-rich programmable zones:
- 4 in XP400 -or- 6 in XP600
- Support all Gemini wireless transmitters
- using Gemini GEM-RECVXP8
- Includes multilingual LED keypad (suffix -SN for Spanish language zone dir'y); RP-X4 for XP400 or backlit RP-X6 for XP600
- Keyfob support: 2 or 4, respectively
- Plus 4 or 8 pts, respectively, for RF points from choice of PIR, window/door & alassbreaks
- Plus XP600's 2-wire fire zone also supports 4 wireless Gemini smoke detectors
- 4 or 6 Individual user codes, respectively
- Available in 4-Paks with 4 keypads, part no. XP400/4 or XP600/4

Comparison of Gemini® panel features & accessories

FEATURES CEMINI ALARM DANIELS							
FEATURES	GEMINI ALARM PANELS						
	GEM-P400	GEM-P800	GEM-P801	GEM-P816			
ZONES ON BOARD	(acts as) 4	(acts as) 6	8	8			
MAX. # ZONES	4	6	9	16			
ZONE EXPANSION (NOTE: Each Custom Alpha Keypad adds 4 Built-in Zones) (2 on RP8LCD)	-	2 Wireless Only Zones	2 Wireless Only Zones	2xGEM-EZM4/8 1xGEM-EZM8			
USER CODES	4	8	8	16			
# OF FIRE ZONES; 2 WIRE FIRE	-	1 2/4 WIRE	1 2/4 WIRE	UP TO 16; 2 2-WIRE			
KEYPADS OR USER INTERFACES SUPPORTED	4(total) GEM-RP4 or GEM-K400 IREMOTEMOD/12	4(total) 4(total) GEM-RP8 GEM-RP8 RP8LCD or RP8LCD or GEM-K800 GEM-K800 IREMOTEMOD/12 IREMOTEMOD/12		7 (total) GEM-RP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF K4 -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen			
EVENT LOG	-	50	50	256			
# OF AREAS	1	1	1	1			
# OF OUTPUTS	2	2	2	3			
# OF WIRELESS RECEIVERS SUPPORTED	2 (GEM-RECVXP8 only)	2 (GEM-RECVXP8 only)	2 (GEM-RECVXP8 only)	2 (GEM-K4RF, RECV32)			
# WIRELESS POINTS	4	8	8	16			
# WIRELESS KEYFOBS	2	4	4	8			
AUTO ARM	-	-	-	YES			
OPEN/CLOSE SUPPRESSION	-	-	-	YES			
AUTO DISARM	-	-	-	-			
SCHEDULES	-	-	-	-			
LINE CUT DETECT	YES	YES	YES	YES			
BELL SUPERVISION	YES	YES	YES	YES			
COMMUNICATION FORMATS	CONTACT ID; 4/2	CONTACT ID; 4/2	CONTACT ID; 4/2	CONTACT ID; 4/2, SIA			
INPUT POWER	16.5 VAC	16.5 VAC	16.5 VAC	16.5 VAC			
MAX STANDBY CURRENT	350mA	500mA	650mA	650mA			
ALARM CURRENT	2 AMPS	2 AMPS	2 AMPS	2 AMPS			
	GEM-P400/4 4 Pak of Controls, Keypads & Transformers	GEM-P800 Control, Keypad & Transformer	GEM-P801 Control, RP8 Keypad & Transformer	GEM-P816 Control & Transformer.			
		GEM-P800PAK Control, Backlit GEM-RP8 Keypad, Transformer, Siren, PIR 1500, Jack, Cord, 4AH Battery	GEM-P801ALPHA Control, Custom Alpha RP8LCD Keypad & Transformer	816PERFPAK Control, GEM-RP3DGTL Keypad, Transformer Also, K816PERFPAK, same but w/ GEMK3DGTL stay away style keypad			
AVALABLE IN THESE		GEM-P800PAK2 Control, Backlit GEM-RP8 Keypad, Transformer, Siren, PIR1680, Jack, Cord, 4AH Battery	801LCD-SUPERSVR Control, Custom Alpha RP8LCD Keypad, Siren, PIR1680PT, Jack, Cord, 4AH Battery & Transformer	816PERFPAKPLUS Control, GEM-RP3DGTL Keypad, Transformer, Siren, PIR, Jack, Cord, 4AH Battery Also, K816PERFPAK, same but w/ GEMK3DGTL stay/away style keypad			
CONFIGURATIONS			801KSUPERSAVER Control, K800 LED Keypad w/Stay/Away Keys, Siren, PIR1680PT, Jack, Cord, 4AH Battery & Transformer	816PREMPAK Control, GEM-RP1CAe2 Keypad, Transformer Also, K816PREMPAK , same but w/ GEM-K1CA stay/away style keypad			
			801 SUPERSAVERPK as above but with RP8 LED Keypad with classic RP Keys	K816RFPAK Control, GEM-K4RF Keypad w/ built in 32-pt RF Receiver and stay/away style keys, Transf.			

GEMINI ALARM PANELS							
GEM-P1632	GEM-P1664	GEM-P3200	GEM-P9600	GEM-X255			
8	8	8	8	8			
32	64	32/48	96	255			
6xGEM-EZM4/8 3xGEM-EZM8	GEM-EZM4/8 GEM-EZM8	3xGEM-EZM8	3xGEM-EZM8 1xGEM-EZM8	GEM-EZM8 31xGEM-EZM8			
32	64	48	96	195			
UP TO 32; 2 2-WIRE	UP TO 64; 2 2-WIRE	UP TO 32; 2 2-WIRE	UP TO 96 WITH UP TO 8 2-WIRE FIRE	UP TO 255 WITH UP TO 8 2-WIRE FIRE			
7 (total) GEM-K1VPS, K1V, RP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF K4 -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen	7 (total) GEM-K1VPS, K1V, RP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS or DK1CA DK3DGTL, K3DGTL K4RF K4 -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen	7 (total) GEMRP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF K4 -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen	15 (total) GEMRP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF K4 -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen	15 (total) GEM-RP1CAe2 GEM-K1CA GEM-DK1CA -PLUS- IREMOTEMOD/12; iBR-TAB Touchscreen			
400	400	800	800	800			
2	4	2	8	8			
3, UP TO 11 (Using RB3008 Relay Modules)	3 UP TO 16 (Using RB3008 Relay Modules)	3, UP TO 27 (Using RB3008 Relay Modules)	3, UP TO 99 (Using RB3008 Relay Modules)	3, UP TO 99 (Using RB3008 Relay Modules)			
2 (GEM-K4RF RECV32/96)	2 (GEM-K4RF RECV32/96)	3 (GEM-K4RF RECV32/96)	4 (GEM-K4RF RECV32/96)	4 (RECV32/96/255)			
32	64	48	96	255			
8	8	8	16	16			
YES	YES	YES	YES	YES			
YES	YES	YES	YES	YES			
-	-	YES	YES	YES			
-	-	255	255	255			
YES	YES	YES	YES	YES			
YES CONTACT ID; 4/2, SIA	YES CONTACT ID; 4/2, SIA	YES CONTACT ID; 4/2, SIA, Modem II	YES CONTACT ID; 4/2, SIA, Modem II, (RS232 output option)	YES CONTACT ID; 4/2, SIA, Modem II, (RS232 output option)			
16.5 VAC	16.5VAC	16.5 VAC	16.5 VAC	16.5 VAC			
650mA	650mA	650mA	750mA	750mA			
2 AMPS	2 AMPS	2 AMPS	2 AMPS	2 AMPS			
GEM-P1632 Control & Transformer	GEMP1664 Control & Transformer	GEM-P3200 Control & Transformer	GEM-P9600 Control & Transformer	GEM-X255 Control & Transformer			
1632PROPAK Control, GEM-RP3DGTL Keypad, Transformer Also, K1632PROPAK, same but w/ GEMK3DGTL stay away style keypad	GEMP1664VPSPK 4-area control, Multifunction LCD Coded Talking Keypad w/built in UL siren, occupancy sensor and 25'Pet PIR (GEM-K1VPS); transf.	Optional Mercantile Housing, H1217 or w/unit GEM-P3200M	Optional Mercantile Housing, H1217 or w/unit GEM-P9600M				
GEM-K120PAK Control, Fixed LCD Keypad w/ built in 32pt RF Receiver and stay/away style keys, Siren, PIR1680PT, Jack, Cord, 4AH Battery, Transf.	GEMP1664DK1PK 4-area control, in oversized locking enclosure, Door-Style Keypad (GEM-DK1CA), transf.						
1632INTROPAK Control, GEM-RP1CAe2 Keypad, Transformer Also, K1632INTROPK, same but w/ GEM- K1CA stay/away style keypad	IREMOTE64PAK 4-area control, Virtual Keypad Module (iRemoteMod/12), Multifunction LCD Coded Talking Keypad w/built in UL siren, occupancy sensor and 25'Pet PIR (GEM-K1VPS); transf.						
K1632RFPAK Control, GEM-K4RF Keypad w/ built in 32-pt RF Receiver and stay/away style keys, Transf. GEM1632RECVPAK Control, GEM-RP1CAe2 Keypad, Conventional 32 Pt. RF Receiver (GEMRECV32), Transf.							

NAPCO Alternative Alarm Reporting Solutions:

Up/Downloadable GSM Alarm Communicators



StarLink Up/Downloadable GSM Alarm Communicator - The Ultra-Economical, Advanced Radio with Signal-Boost™ for unsurpassed reliability anywhere

SLe-GSM

- Affordable enough to standardize on for every account, so telco is no longer a concern, today or in the future -use for primary or backup reporting
- Full High-Speed Napco Panel remote uploading/down-loading (2-way communications) --Amazing panel down-loads in under a half-a-minute! Supports GEMP816, 1632, 1664, 3200, 9600, X255, GEMC burg.
- Exceptional reliability everywhere Signal-Boost circuitry filters and amplifies alarm signals and wave shapes for performance even in remote/fringe areas using special antenna design and communicator module
- 1-Step enrollment and programming built in, ready for most jobs - Automatic dialer-capture technology eliminates time-consuming web setup!

- Ability to change radio's designated reporting phone numbers without re-downloading from the panel
- Advanced program options too; including Email/Text/ SMS messages alerts
- Universal full event reporting from any panel, using Contact ID or 4/2, virtually anywhere to any Central Station (with no special equipment)
- Remote arm/disarm any panel brand with a keyswitch input
- Includes SIM card and dual band high-efficiency antenna
- Remote signal-strength and diagnostic LEDs viewable at a glance
- Low/No-current draw module options

ORDERING INFORMATION

SLE-GSM GSM Communicator, SIM card (monthly GSM service sold separately www.Napcocomnet.com)

PCD2000 Quickloader v6.0.2 software or better required for downloading

SLE-DLCBL Dowloading panel-to-radio cable

SLE-DLEXT Optional, for up/downloading, extends distance from radio to panel, from 10′, up to 100 ft.

SLE-SMTCHG Optional, Smart Charge Module. Allows for optimal radio position regardless of available AC outlets. Also ideal where auxiliary (fire) standby power is too low-without requiring a separate power supply. Uses standard 4AH/12V rechargeable battery.

SLE-ATT/4 Optional 4-pack of upgrade SIM cards

SLE-GSMET GSM Communicator in metal housing (also accommodates 4 Ah /12V rechargeable battery), SIM card included.


NAPCO Alternative Alarm Reporting Solutions:

Internet Alarm Communications

NetLink™ Alternative Alarm Reporting & VoIP Solution

NetLink Panel Modules NL-MOD & NET-COMM

- Communicate alarms via Internet or intranet over a TCP/ IP-based network using dynamic IP addressing
- Secure transmissions over the Internet using AES128bit encryption
- Use for primary and/or backup reporting
- NL-MOD NetLink Module can be used with any Napco panel, from the GEMP816 to the X255 and Gemini-Commercial (GEM-C) to securely communicate alarms, status, supervisories, etc, pinopointed by-zone
- NET-COMM Economy NetLink Module, is similar, and this less expensive communicator is driven directly by the alarm panel. It supports 5 channel reporting codes, communicating, for example, alarms, panics, fire, telco failure, low battery, etc.





NetLink Receiver for UL Central Station applications:

NL-RCV-RMPCUL

- Both NetLink modules report via TCP/IP to any central station or intranet facility with the NetLink UL Listed Receiver (model NL-RCV-RMPCUL)
- UL864/UL1610-listed advanced, rack-mounted receiver
- Interfaces with the conventional Central Station automation system
- 2 Reception Modes: Automatic Mode, where alarm signals are sent normally to the automation system for processing -or- Manual Mode, used when direct operator interaction is desired, using the built in menu-driven keypad-style alphanumeric interface
- For redundant/mirrored applications -Two can be simply crossover-cable networked
- Compliances: UL864 (Control Units for Fire Protective Signaling Systems); UL1610 (Central Station Burglar Alarm Units).

Gemini Access: Add Access Control to Gemini Alarms from the P3200 to Gemini-Commercial GEMC



Integrate Access with Intrusion Systems:

- Cost efficient access solution, easily added & installed, affordable for even small to mid-size installs
- Seamless Integration with Gemini Control Panels GEMP3200, P9600, X255, GEMC; easily programmed with Napco Quickloader (single site programming and shared database)
- Supports HID & Gemini Prox Cards and Readers (both offered in moneysaving kits)
- Optional PCD-Manager enduser software for corporate security or personnel departments, etc. Easy-to-use enduser Windows-based package for account management and self-maintenance provides limited enduser account control: Manage database of both alarm users and up to 1000 access control cardholders, logs, schedules, access groups, etc.(see right).
- Plug and play GEM-ACCESS comes ready with its own enclosure, power supply (aux. for prox readers and mag locks) and battery backup. (GEM-ACMID)
- Fast card processing transaction speeds
- Easily expandable by-door with affordable GEM-2D Plug-in PCBs
- Supports HID or Gemini Prox (GEM-PX) Cards & Readers

Gemini Access

Ordering Information:

GEM-ACM1D Access Control Module for 1 door module in metal enclosure, w/ power supply, transformer and software enhancement upgrade EPROM for Gemini alarm panel.

GEM-2D 2nd Door plug-in PCB, for use in above.

GEM-1DKIT Economical GEM-PROX Kit Module in enclosure, w/power supply, transformer, panel prom, GEM-PX prox reader with status LED indicators, 25 Gemini prox cards.

GEM-1DKITA HID reader kit, as above, with HID Reader and 25 HID 1326 prox cards

GEM-PX Gemini prox reader with access and alarm status indicators **GEM-PXC/50** 50 Additional Gemini prox cards

GEM-H1326 HID prox peader

GEM-H1326C/100 100 Additional HID cards

PCD-MANAGER Optional on-site mgt. software, v.3.0 (below)


Gem-Access' **PCD-Manager v3.0** enduser software for client security/ personnel departments

Increases ID cardholder capacity to 1000

Napco's GEM-ACCESS Alarm/Access Control Integration System, supported by the GEMP3200, P9600 & X255 and GEMC Security Panels, enables you to offer your accounts optional Windows-based software to give their security and/or personnel



departments limited control of their premises' alarm and access systems and authorized users, while safeguarding your system configurations, dealer codes, account ID's, central station number, etc. safely away from view. Plus, dealers can personalize the look of the account's software to represent their company, including options for uploading alarm company logos, website, tech support contact info., etc. with easy-to-use dealer customization utility built in.



GEM-ACMID adds integrated access control to the burglar alarm functions of the GEMP3200, 9600, X255 and GEMC Gemini-Commercial Systems

Gemini Access: PCD-Manager (cont'd)

Easy account self-management interface for routine tasks, like adding alarm users/ID cards


- Easy personnel management for both alarm users (keypad user codes) & ID access cardholders
- Adding/editing/deleting personnel
- Importing text file names/data (including those from personnel files)
- Now supports the Windows Quickloader "Extended Export Files", so you can import cards and personnel directly from the Windows Quickloader.
- Viewing event logs
- Create and manage up to 195* access groups via intuitive dropdown menus and helpful screens (*see capacities chart, right)
- Assign users and/or access groups to easy-to-set schedules with pop-up calendar selections, drop-down menus, etc.
- Helpful Finalize Changes Summary screens summarize changes in a data-entry session for review before changes are made and downloaded.

- Comprehensive error-checking utility helps avoid errors and flags conflicts
- Report Print Manager Alarm system users/info., cardholders, scheduled events & holidays & logs.
- Easy PCD-Manager link to panel via all standard Napco download modes (locally via serial COM port; remotely via telco line or remotely via TCP/IP network)

Gemini Access capacities, maximum by panel

Panel	Doors	Access Groups	Total Cards &/or Alarm Users	Expanded Cardholders (w/ PCD-Manager)	
GemC	8	195	195	1000	
X255	8	195	195	1000	
P9600	8	96	96	1000	
P3200	4	48	48	1000	

Napco Universal Keyfob/Keyfob-Receiver Kits:



Bi-directional LCD keyfob compatible with all major alarm panel brands

2WAY-UNIVKFKIT

- Bidirectional keyfob with LCD status icon display and sounder.
- System Status is indicated on its LCD display with 8 intuitive icons (a lock, a house, a flame, etc.) plus corresponding audible beeps
- Universal panel compatibility with most major control panel brands, using bus or keyswitch input (including bus operation on NAPCO's Gemini & Magnum plus Honewell)
- Complete kit with dedicated 2-way Keyfob Receiver and one fob in **2WAY-UNIVKFKIT**; or add on up to 6 more fobs, sold separately **2WAY-UNIVKF**

Universal value keyfob... works with any alarm panel brand with keyswitch

UNIVKIT1

- Simple 2-button Arm/Disarm operation with LED indicator; optional panic
- Works with all control panel brands with keyswitch input
- Long range yet compact
- Complete kit with dedicated Keyfob Receiver (1-way) and one fob in UNIVKIT; or add a second keyfob (max. 2), sold separately UNIVKF1

Gemini Wireless: Proven to outperform the competition



Napco's crystal-control Gemini wireless products have been proven by an independent testing laboratory to outperform competitive products, with long-range RF reliability, as much as 50% higher than other top brands.

Gemini Transmitters range from keyfobs and panic buttons, to recessed door and surface-mount window/door contacts, to wireless PIR, PIR/pet and dual sensors, and from wireless smokes and glass breaks to heat detectors. Simply put, Gemini's uncommon crystal-control precision and omnidirectional circuitry, ensures the wireless/hardwire systems you provide your customers will dependably deliver the security and trouble-free, peace-of-mind they deserve for many years to come.



Advanced performance Gemini RF receivers

GEM-RECV-XP8 8 Points For Express, P801/800/ P400 panels, only **GEM-RECV-32** 32 Points

GEM-RECV-96 96 Points **GEM-RECV-X255** 255 Points

- Dual diversity antennas minimize nulls & enhance reliability
- Tamper- and RF-jamming supervision
- Separate programmable supervisory times by device type
- Audible fault-find mode in walk test
- Also, fixed English language keypad GEM-K4RF with built in 32 pt receiver (see keypads section).

Low profile wireless window/door transmitter

GEM-TRANSLP

- Ultra compact design, 2.5 x 1 x 0.4 (H x W x D inches)
- Tamper supervised
- Replaceable lithium PL2032 coin cell battery (supplied
- 5-year battery life, typical
- Magnet and Internal reed switch
- External lead (24" mini connector pigtail) for wiring external devices (jumperselectable)
- Magnet mounts with either supplied double-face tape or screws (screwtabs easily removable from mounting plate, at score)



Now in Brown, too, **GEM-TRANSLP-BRN**





GEM-TRANSLP virtually disappears even in slimline window frames

Recessed wireless window/door transmitter

GEM-RTRANS (not shown)

- For recessed use in both windows and doors
- Powerful wireless transmitter
- White housing, magnet & hole cover
- Field-replaceable 5 year battery. Long-life 3V type DL123A lithium battery supplied.

Wireless window/ door transmitters

GEM-TRANS2 2-Points

- Soft white, compact, low profile
- Reversible mounting position for left or right handed operation
- Low battery clearly displayed at keypad by zone and transmitter number
- Both models include built-in reed switch, magnet, lithium battery, tamper and terminals

GEM-TRANS2BRN25

 Field-changeable brown housings for woodgrain installation (case of 25).

Wireless acoustic glass break detector

GEM-GB

- Superior-immunity to false alarms and excellent detection, even through blinds & light drapes.
- Pattern recognition technology - recognizes the actual pattern of glass breaking across the full audio band.
- 25' coverage radius with automatic test for easy installation
- Enduser hand clap sensor verification
- Includes lithium battery, tamper & mounting kit

Wireless Adaptive® dual microwave/PIR

GEM-DT

- Broad 40′ x 40′ range
- Exclusive Adaptive dual technology for superior false alarm resilience-even from animal/ pet activity and optimized catch.
- Active self-test of both sensors
- 5 interchangeable lens patterns
- One button walk-test with auto shut-off
- 3 distinct transmissions for tamper alarm and self-test failure
- EMI/RFI protected with fullyshielded SMD circuitry
- Includes batteries, tamper and mounting screws

Wireless PIR & Pet PIR

GEM-PIR

- Broad 50′ x 50′ coverage
- 11 interchangeable lenses
- Signal selective processing
- Auto temperature compensation
- EMI/RFI protected with fullyshielded SMD circuitry.
- Battery-saver feature
- Includes lithium batteries and mounting screws

GEM-PIRPET

As above with 40 lb. pet/animal immunity









Wireless photoelectric smoke detector

GEM-SMK

New & improved! Designer styling and longer battery life

- Long 5-year battery life, typ. (batteries included)
- Compact 5.2 inch diameter; attractive decorator white
- Built-in silence feature and test button
- Visual LED indicates alarm & standby
- Audible/visual indicator for low battery and need for detector cleaning
- Proven Gemini ™ wireless crystalcontrolled transmitter





Wireless heat detector

GEM-HEAT

- High-quality 135°F (57° C) fixed temperature detector with rate of rise
- Reliable, crystal-controlled wireless technology
- Long-life, replaceable lithium batteries

Wireless keyfob/ emergency pendant transmitter

GEM-KEYF compact style

- 4-Button operation: 2 for On/ Off of security system and 2 programmable for Aux. functions, e.g. panic, medical, relays or relay groups, instant or X-10 control
- Visual indicator fortransmission or low battery
- Includes keyring, chain, replaceable battery, alternate icon key set for automation (lights)

Wireless waterproof panic

GEM-WP PANIC

- Waterproof personal panic button
- Worry-free peace of mind
- 1-button operation with tactile feedback click
- Extra-large, soft touch button for trouble-free use even by dexterity-impaired or arthritic hands







How to Build a Winning Gemini System.









GEM-WPPANIC WATERPROOF PANIC



GEM-KEYF KEYFOB



GEM-TRANSLP LOW PROFILE WINDOW/DOOR -LESS THAN 1/2" D



GEM-TRANS2 WINDOW/DOOR



GEM-PIR/ GEM-PIRPET PASSIVE



GEM-DT DUAL TECHNOLOGY



GEM-RTRANS RECESSED WINDOW/ DOOR



GEM-GB ACOUSTIC GLASS BREAK



GEM-SMK SMOKE



GEM-HEAT DETECTOR



		GEMINI PANELS							
		GEM	P816	P1632	P1664	P3200	P9600	X255	P801
		K1CA/DK1CA	•	•	•	•	•	•	
	STAY & AWAY	K1VPS		•	•				
		K2AS	•	•	•	•	•		
GEMINI KEYPADS		K3DGTL/DK3DGTL	•	•	•	٠	•		
YP/		K4RF	•	•	•	٠	•		
KE		K4	•	•	•	•	•		
Z	CLASSIC	RP1CAe2		-		٠	•		
GE		RP2ASe2		-		٠	-		
		RP3DGTL		-		٠	-		
		RP8LCD							
		RP8/K800							•









Napco Wired Motion Sensors: 20+ years of innovation inside





Patented Adaptive® slimline sensor and long-range version

C100STE & long-range model C100STLRE

- C-100STLRE 30' x 35' range C-100STLRE 50' x 40' range
- Proven, patented adaptive technology continuously monitors the environment, counteracting false alarms and re-sensitizing to optimize intruder catch
- Active self-test supervision of both microwave & PIR channels
- Wide array of interchangeable lenses
- Secured cover; tamper-supervised

Napco patented Adaptive® Microwave/ PIR Sensors virtually make all other motion sensors, dual technology or otherwise, obsolete. Once they're installed, they're like having a technician on-site, making all adjustments for you 24-hours a day.

These exclusive sensors are the only ones on the market that actively & continuously monitor their environment 24/7, counteracting false alarms and re-sensitizing themselves to continually optimize catch performance. In fact, some models will even notify you if they have been purposely or accidently blocked or masked.

Ideal in all installations, despite harsh environmental conditions and/or pet/rodent activity, they provide the best protection available from both intruders and false

They pay for themselves with the first service call they prevent.

Commercial Adaptive sensors with mask/block supervision

M7100STE

- 40′ x 40′ range
- Active self-test supervision of both microwave & PIR channels
- Alarm memory with exit/entry delay
- Wrap-around shielded circuitry
- Wide array of interchangeable lenses
- 3' Dome of Protection™ for anti-masking &
- anti-blocking supervision
- Secured cover
- Tamper-supervised

M7300STE

M7100STE features plus:

- 70′ x 60′ range
- Tamper switch

Adaptive heavy-duty industrial-strength sensor

M9000STE

M7300STE features plus:


- Trio-range from 55° to 120'
- EZ aim, positive locking swivel bracket
- Concealed wiring channel
- Vandal-resistant industrial/institutional strength housing
- 3' Dome of Protection anti-masking/antiblocking supervision

Microwave/PIR Detectors continuously adjust to their environment, providing 100lb. pet/animal immunity and ultimate reliability & false alarm protection

C200AP with P.E.T.™

The best pet immunity for any size animal

- P.E.T. ™, Profile enhanced targeting circuitry provides up to 100lb. (45.36Kg) pet immunity
- 40' x 40' maximum broad range
- Compromise-free intrudercatch and false alarm protection - ideal when the pet leaves the room, too. Dynamic adaptive



- Smarter Systems™ panel & sensor integration input
- Superior RFI/EMI lightning protection with wrap-around shielded SMD circuitry
- Twin-Tee fluorescent light interference filter
- Self-test
- 2 Field-changeable lenses supplied
- Range control & auto-temp compensation



Feature-packed advanced passive infrared sensors

Microprocessor PIR with 65lb pet immunity & built-in room-temp alert

PIR1680PT

- 45′ x 45′ range
- 65lb pet/animal immunity
- Room-temp alert temperature monitoring provides auto-alert at 40°F - 90° F
- Look-down/creep zone
- D.C.I.D. Technology- detect & compare imaging diagnostics for advanced false and true alarm detection
- Active self test mode
- Exceptional RFI-/EMI/lightning shielding of key components
- Lens bank available, including long range, barrier, and specialty ranges
- Wall or corner mountable
- Tamper supervised
- Form A relay

PIR1680

 Standard model as above, but with 20lb. pet/animal immunity



Advanced 70' PIR

PIR1710

- 70' x 60' Broad range coverage perfect for both residential and commercial
- Features look-down/creep zone
- SSP™ (Signal Selective Processing) for the easiest and most stable of installations
- Auto temp compensation
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
- Wall or corner mountable
- Excellent EMI-/RMI-/lightning protection with resilient SMD circuitry
- Tamper supervised
- Form A relay

Economical PIR sensor with look-down

PIR1510

- 30′ x 30′ broad range coverage
- Attractive, super-compact size
- SSPTM (Signal Selective Processing) for the easiest and most stable installations
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
- Long-range, barrier and specialty lenses are available to suit all coverage needs
- Wall or corner mountable, with horizontal and vertical adjust
- EMI-/RMI-/lightning protection with resilient SMD circuitry
- Form A relay
- PIR1500 version also available, as above, without look-down/creep zone.



The pet-immune PIR with Quick-Catch that profiles false alarm sources and virtually installs itself

For decades, NAPCO's innovative technology has produced sensors with superior false alarm discrimination. Today NAPCO is a leader in smart PIR technology, P.E.T. immunity, and décorenhancing design.

IQ PROFILER™

- 50lb. pet immunity (22.7Kg) & superior false alarm discrimination with unique dual focal lenses.
- Installation in a snap with patented Quick-Mount and Quick-Wire terminals
- Maximum range: 50' x 50'
- New & improved quick-catch mode
- Décor white bi-optic contour case and dual focal lenses provide exceptional distance profiling
- Far field lens allows for detection of large objects and ignores small targets nearby
- Near field lens allows for discrimination of small targets nearby
- Shielded high-performance aspheric lenses plus look-down/creep zone
- Sensor chamber prevents insect, draft, and dust interference.
- 20V/m RF-shielded circuitry









IQ VISION Advanced PIR with "IQ Look" and now all-white styling

- 40' x 40' range; 30lb. pet immunity
- Features look-down/ creep zone
- SSP™ (Signal Selective Processing) for the easiest and most stable of installations
- Auto temp compensation
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
- Excellent EMI-/RMI-/lightning protection with resilient SMD circuitry
- Tamper supervised
- Form A relay (Form C option)
- Long-range, barrier and specialty lenses are available to suit all coverage needs
- Wall or corner mountable, with horizontal and vertical adjust



Napco Access: Robust, scalable access control systems for 2 to 128 doors



NapcoAccess™ Access Control Systems are full-featured, easy-to-use systems and can be integrated seamlessly with or without Napco Gemini Alarm Systems. The full line consists of NAX-200X Controllers, AccessPro™ Software and optional Badger Video Badging Software. The system is easy for security professionals to implement, supporting many reader options and boasting reliable, lowmaintenance access panels and simplicity for the enduser.

ORDERING

NAX-200X 2-Door access controller w/power supply

- 2 doors, expandable up to 128 doors
- Integrates seamlessly with Napco Gemini Alarm Systems (GEM-P3200, -P9600, X255, Gemini Commercial (GEMC).)
- Includes serial communication cable for PC-to-panel connnection
- Also supports network/LAN commmunications using optional NAX ENET ethernet adapter

NAX-200XIO Input/Output Expander

 16 supervised inputs, 16 relay output expansion board and enclosure

NAX-200XIOBD Board-only version

NAX-2000 Access Software, 5 workstations

 For up to 10,000 cardholders, 256 access groups, permits up to 2 access groups per badge

- Features custom personnel fields,
 128 schedules, 50 holidays
- Built-in system configuration templates for quick starts



NAX-BADGE Optional Badging Software

 Badger photo badge creation software with easy to use templates for use with Access Pro software

NAX-KIT-A HID Starter Kit with: NAX-200X 2-door access panel, PC-to-panel serial

comm. cable, Access Pro Software, 2 HID ProxPoint Plus Readers, 50 HID Prox Card II.

NAX-KIT-PX GeminiProx Starter Kit, as above, but with 2 Gemini Prox Readers and 50 GEM-Prox proprietary cards (shown, in inset). GEM-PX Readers are economical, weatherproof readers with unique alarm system status LEDs, enabling users to access the door and disarm the system with an ID prox card! Plus, LED indicators enable users to know alarm system status before arming.

Napco Commercial & Government Solutions





Integrated Intrusion • Fire • Video • Access • Locking

- Innovative integrated enterprise class solutions reliable, high-quality security, life-safety, video, access
 and/or locking technologies integrated in one scalable
 interoperable platform called Napco FUSION™.
- Comprehensive Expert Support for endusers, architects and engineers, security consultants and commercial integrators
- Professional Tools, Training & Communications A growing list of the latest design support tools, CSI specifications, CAD diagrams and configuration aids are available on a dedicated website. An expert online support forum ensures continuous news and information is disseminated. Accredited training is provided in the field and in live and archived webinar modules online.:
- Strong Security Heritage Napco Security Technologies, Inc. (NASDAQ: NSSC) has been solely dedicated to developing and manufacturing innovative security solutions since its founding in 1969.

- Industry-Leading Brands Napco Commercial™
 Gemini™, Continental CardAccess®, Alarm Lock Trilogy®, Networx™and Marks-USA™
- Commitment to Quality ISO9001:2000 Certified and subscribing to a rigorous quality management system, Napco products are precision-manufactured to meet or exceed industry specs.
- Built to Last Napco stands behind its products with among the longest warranties in the industry and even legacy systems are often field upgradable for lowest maintenance costs. Today, millions of people, businesses, institutions & residences around the world are protected by Napco products.

Napco Fusion™ Platform is a unique total integrated security solution for intrusion, fire, video, access & locking.



Napco Security Technologies introduces the new Napco Fusion™ total security solution, built on a heritage in professional security, developing innovative, reliable security technology, including some of the industry's best-known brands: Napco Gemini, Continental CardAccess®, Alarm Lock Trilogy® and Marks USA. Today, together in one flexible customizable platform called Napco Fusion™, all Napco's synergistic technologies combine in one sophisticated, simplified "total integrated security solution", providing seamless, near interoperability of intrusion and fire protection, video, access control & locking.

- Scalable, modular enterprise-class platform for intrusion, fire, video, access and locking
- 2 to thousands of doors, unlimited users, at one or many global sites
- Lowest acquisition and maintenance costs
- No annual software licensing fees
- Wired, wireless or hybrid system, for lowest installation cost in any type of building
- Comprehesive high-speed access control processing & 1/2-second door open times
- Multi-card, PIV, biometric, & keypad support
- Complete DVR/NVR and camera control, on-demand and video archiving video

- Napco Commercial[™] Intrusion, Fire and UL Commercial Wireless Alarm Integration
- Integration with Trilogy® Wireless Networked pushbutton/HID® Prox access locks (ethernet or 802.11 global comm.)
- Integrated realtime event linking, mapping, scheduling & logging of alarms, video, access control & locks
- Threat level & visitor management
- Secure TCP/IP reporting option; AES encryption up to 256bit
- Remote-control web client
- Remote managed services for incremental recurring montly revenue

- Intrusion
- Fire
- Video
- Interactive Online Services
- Access control



www.napcosecurity.com/newproducts.html

1-800-645-9445 salesinfo@napcosecurity.com 333 Bayview Ave., Amityville, NY 11701

Complete access control hardware & software solutions featuring:

- Integrated use with Trilogy Networx Locks
- DVR/NVR & alarm integration
- Visitor & threat level management
- Time & attendance; payroll & badging
- Elevator control
- Remote-control web client
- Dynamic mapping
- Multi-card, biometric and reader support
- FIPS/TWIC/CAC support



www.continentalaccess.com

631-842-9400 salesinfo@cicaccess.com 355 Bayview Ave., Amitville, NY 11701

- Standalone electronic access locks, PIN code & prox ID card
- Wireless advanced networked locks, Ethernet or 802.11 global communications
- Alarmed exit devices & door alarms



www.alarmlock.com

1-800-ALA-LOCK

salesinfo@alarmlock.com 345 Bayview Ave., Amitville, NY 11701

- Architectural locking hardware & custom locksets
- Life safety locks
- Electrified locksets
- Ornamental iron & woven wire gate locks
- High security cylinders



www.marksusa.com

1-800-526-0233 salesinfo@marksusa.com

365 Bayview Ave., Amitville, NY 11701





1-800-645-9445 · www.napcosecurity.com

NAPCO • ALARM LOCK • CONTINENTAL ACCESS • MARKS USA
333 Bayview Avenue • Amityville, New York 11701 • ++ 631 8429400 • Fax: 631-789-9292
NASDAQ: NSSC

A402J